

Deka GEL Batteries

Deep cycle batteries for Marine, RV, Inverter, EV (Electric Vehicle), Golf Cart, Renewable Energy, Solar Panel (Photovoltaic), and Alternative (Alternate) Energy Applications.

Click Here To Download The Complete Deka GEL Specifications

(** Click to download and save on your computer. PDF format. Adobe Acrobat viewer required for viewing.)

Deka GEL Deep Cycle Batteries

12V	Model	Amp Hrs @ 20 HR Rate	32° F CA	0° F CCA	Reserve Cap. 25 Amps	Length	Width	Height	Weight
	8G24	73.6	575	410	140	10 7/8 in 276 mm	6 3/4 ln 171 mm	9 7/8 in 251 mm	52 lbs 23.6 kgs
	8G27	88	700	505	170	12 3/4 in 324 mm	6 3/4 in 171 mm	9 7/8 in 251 mm	62.7 lbs 28.4 kgs
	8G30H	97.6	640	450	190	12 15/16 in 329 mm	6 3/4 ln 171 mm	9 3/4 in 248 mm	69.5 lbs 31.5 kgs
	8G31DT	97.6	780	550	190	12 15/16 in 329 mm	6 3/4 in 171 mm	9 3/8 in 238 mm	69.5 lbs 31.5 kgs
	8G4D	183	1245	970	395	20 3/4 in 527 mm	8 1/2 in 216 mm	10 in 254 mm	127 lbs 57.5 kgs
	8G8D	225	1470	1150	500	20 3/4 in 527 mm	11 in 279 mm	10 in 254 mm	157 lbs 71.1 kgs
8V	8G8VGC	140	575	400	270	10 1/4 in 260 mm	7 1/8 in 181 mm	10 7/8 in 276 mm	69.5 lbs 31.5 kgs
6V	8GGC2	180	850	585	375	10 1/4 in 260 mm	7 1/8 in 181 mm	10 7/8 in 276 mm	68.4 lbs 31 kgs



Deka GEL 8G24 (8G24M)

Deka GEL 8G27 (8G27M)

Deka GEL 8G30H (8G30HM)

Deka GEL 8G31DT (8G31DTM)

Deka GEL 8G4D (8G4DM)

Deka GEL 8G8D (8G8DM)

Deka GEL 8G8VGC

Deka GEL 8GGC2 (8GGC2M)

Deka GEL Benefits:

- Valve-Regulated
- Gelled-electrolyte
- Sealed construction eliminates periodic watering, corrosive acid fumes and spills
- Increases durability and deep cycle ability for heavy demand applications
- Less than 1% per month stand loss means little deterioration during transport and storage
- Rated non-spillable by ICAO, IATA and DOT
- Transports easily and safely by air. No special containers needed
- Made in the U.S.A.